



bio pin Boat Varnish

DESCRIPTION: bio pin Boat Varnish is a traditional, heavy duty, marine grade, Tung Oil based varnish. Its ingredients contain high performance water repellents which protect the timber from water and abrasion. The varnish penetrates deep into the timber and has excellent adhesion properties. It seals all wooden surfaces, both internally and externally. Designed originally for use in the marine industry, Boat Varnish is more than suitable for use on garden furniture, and interior areas which have damp conditions such as laundries, kitchens and bathrooms etc. **High gloss, transparent finish.**

INGREDIENTS: Binding agent of tung oil, and modified colophony resin, citrus oil, and lead free drying agents.

PREPARATION:

1. The timber must be clean, dry and free of grease etc.
2. This product works best on new timber. Any previous coats of varnish should be sanded back. Completely remove any old, loose or flaking paint etc, prior to using Boat Varnish.

APPLICATION:

1. Ensure preparation has been completed first. Stir well. Follow safety instructions on the label. Do not thin. Use only when ambient temperature is above 8 degrees C. Do not apply in direct sunlight.
2. On new timber, a thin coat of oil (such as a 50:50 mix of Tung Oil and Citrus Turpentine) may be used as an initial priming coat if thought necessary. A primer coat is not recommended on previously painted surfaces, unless the previous finish has been completely removed to expose new timber underneath.
3. A thin layer of Boat Varnish should be evenly rolled, brushed or sprayed onto the surface. Allow 12-24 hours to dry. Scuff lightly with fine grade (600 grit) sandpaper once dry.
4. Apply up to 3 coats (4 coats if a priming oil is not used) as above.

COVERAGE: 75—90 ml per square metre per coat on a surface with average absorption properties.

SIZES: 750ml and 2.5 litre containers.

MAINTENANCE: Do not clean with abrasive cleaning agents. Use a mild detergent, or any plant based cleaner. If the surface is worn and requires a recoat, lightly sand the timber first to remove any flaky old or loose varnish etc. Clean and allow to dry before applying 1 or 2 thin coats of Boat Varnish as above.

SAFETY: Keep away from children. Store in a frost free area with the lid tightly closed. May cause irritation to, or an allergic reaction on skin. Use protective clothing and use in a well ventilated area. This product contains **orange oil** (CAS-Nr 8028-48-6). It is flammable and may cause lung damage if swallowed. Show can and label to your health professional, and treat symptomatically. Clean up with turpentine and hot soapy water. **CAUTION: Wash any cloths in hot soapy water, rinse and hang to dry, as they may self ignite if left unattended.**

CONDITIONS: OUR INFORMATION IS GIVEN IN GOOD FAITH, AND IS BASED ON RESULTS OBTAINED FROM EXPERIENCE AND TESTS. HOWEVER, AS THE ACTUAL END USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, ALL RECOMMENDATIONS AND SUGGESTIONS ARE MADE WITHOUT GUARANTEE. NO AGENT OR REPRESENTATIVE OF NATURAL OILS LIMITED HAS THE AUTHORITY TO WAIVE OR ALTER THESE CONDITIONS.

Manufactured in Germany by Biopin, Linumweg 1-8, Jever.

Supplied in NZ by Natural Oils Ltd www.naturaloils.co.nz