



## OLDE STYLE DANISH OIL

**DESCRIPTION** "Danish Oil" has been well known for many years as a traditional oil for finishing timber. Organoil's **Olde Style Danish Oil** is based on the original heavy oil formula which made "Danish Oils" so popular and easy to use. Designed to nourish and preserve timber, without the need for chemicals or petroleum ingredients. Food safe, and suitable for children's toys, playpens, bassinets and cots etc.

**USES:** Internal furniture, doors, windows, feature timbers such as panelling or sarking and exposed beams. Excellent for woodwork and turning. Not to be used on floors, benchtops or in wet areas.

**INGREDIENTS:** Genuine Tung Oil, White Linseed Oil, pinewood oil and citrus oil.

**PREPARATION:**

1. For best results, fine sand timber to 600 - 1200 grit. The finer the better.
2. Ensure the timber is clean, dry and free of sawdust etc.
3. Previous skin forming products (paint or varnish) should be completely removed by sanding prior to oiling.
4. If accessible during the construction or installation process, it is recommended to coat the rear and / or end grain of the timber with one liberal coat of oil.

**APPLICATION:**

1. Ensure preparation has been completed first. Shake/stir well prior and during use.
2. Using a brush or lambswool applicator, apply 2 coats **ONLY**, a minimum of 24 hours apart. (One coat only, when rejuvenating a previously oiled surface).
3. The use of a white synthetic scourer, or fine (1200 grit) wet and dry sandpaper will lift the patina to a low sheen.
4. It is **essential** that within 1 hour of each application, you firmly dry-cloth in the excess oil, to ensure a non tacky, non dust collecting surface.
5. Power buffing with a lambswool pad 24-48 hours later, will also increase the patina.

**COVERAGE:** (Approximate per coat and depending on timber)

Hardwoods:	10 – 14 square metres per litre	(18-20 on the second coat)
Softwoods:	5 – 9 square metres per litre	(8-12 on the second coat)
Pine & Cedar:	2—3 square metres per litre	(6-8 on the second coat)

**SIZES:** 500ml, 1 litre, 4 litre and 10 litre containers.

**MAINTENANCE:** To clean, or prior to re-oiling, wipe surfaces with a solution of warm water and methylated spirits. Use a synthetic scourer to remove grime. Once dry, apply one light coat as above.

**HANDLING:** Store with lid tightly closed in a cool place. Clean up with warm soapy water or pure Gum turpentine. **SOAK CLOTHS IN HOT SOAPY WATER, RINSE AND HANG TO DRY AS THEY MAY SELF IGNITE IF LEFT UNATTENDED.** Keep out of reach of children. Use in a well ventilated area. If swallowed, seek medical advice.

**FLAMMABILITY:** Flashpoint 70 degrees C.

CONDITIONS: OUR INFORMATION IS GIVEN IN GOOD FAITH, AND IS BASED ON RESULTS OBTAINED FROM EXPERIENCE AND TESTS. HOWEVER, AS THE ACTUAL END USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, ALL RECOMMENDATIONS AND SUGGESTIONS ARE MADE WITHOUT GUARANTEE. NO AGENT OR REPRESENTATIVE OF SALES FORCE NSW HAS THE AUTHORITY TO WAIVE OR ALTER THESE CONDITIONS.

Manufactured by SALES FORCE NSW, Sydney, Australia