



DECKING AND EXTERIOR OIL

DESCRIPTION:

A timber finish, sealer and preservative that will nourish and protect external timbers. Contains Tung Oil, and other vital plant oils/extracts, refined bees waxes and UV absorbing oxides. This product is available in 3 colours. "Standard" finishes to a neutral brown; "Red Highlighter" finishes to a red/brown and is suitable for similar coloured timbers such as kwila. "Teak Highlighter" finishes to a warm yellow/gold, and is suitable for lighter coloured timbers such as pine, and Douglas fir. All 3 colours are semi transparent.

USES:

Exterior timber decking, joists, bearers, cladding, pergolas, lattice, railings, fencing and posts. **This product is not suitable for use on tongue and groove verandah decking or internal flooring.**

NOTES:

1. For new decking hardwood timbers such as kwila, eucalyptus, and Fijian Mahogany, which may be high in moisture and tannin content, the use of Organoil's Woodguard is recommended. Refer to this product's data sheet and can for instructions.
2. For joists and bearers—if accessible, or prior to installation, apply one liberal coat. At the same time, apply a coat to the underside of the decking boards. Woodguard could be used as an alternative.
3. For previously finished timbers, Organoil products may not be compatible with synthetic resins, acrylics and emulsions. It is recommended that you wash the timber thoroughly, then sand it back prior to application of the Organoil product.
4. This product has a **MATT** finish. The "Standard" should be used if seeking a neutral/natural effect. However, "Standard" will not give the longevity of colour achieved with the Red and Teak Highlighters.

		1 st coat	2 nd coat
COVERAGE:	Hardwoods	7-10 sq metres / litre	10-14 sq metres / litre
	Softwoods	3-5 sq metres / litre	6-8 sq metres / litre
	Pine & Cedar	2-3 sq metres / litre	5-7 sq metres / litre

SIZES:

1 litre, 4 litre and 10 litre containers.

PREPARATION:

1. Ensure the timber is free of sawdust, cement dust, nails or metal filings etc, which may react with the oil and stain the timber.
2. Ensure the timber is clean (washed and/or sanded) and dry (minimum of 48 hours drying from wet). Do not oil if rain is due.
3. In any event, **DO NOT** apply Organoil products to timber where the moisture content is above the NZ standard of 16%.

APPLICATION:

1. Ensure preparation has been completed first. Shake/stir well prior and during use.
2. Apply 2 coats with a brush or lambswool applicator. Use of a roller is not recommended as they splash oil around.
3. Apply 2 coats (1 only when rejuvenating) a **minimum** of 24 hours apart.
4. It is essential that within 1-2 hours of each application (and when re-coating) you dry brush or cloth in excess surface oil to ensure a non-tacky dust free surface. **DO NOT over apply the oil. 2 coats should be the maximum required. Attempting to build a finish above the timber's surface will not achieve greater protection; it will only result in the surface being sticky, dust attracting and water marking.**

CLEAN UP AND HANDLING:

Hot soapy water or citrus turpentine. **NOTE: If any oil gets onto glass windows, aluminium, steel or plastic etc, remove it before the oil cures, using turps or warm soapy water.** Store with lid tightly closed in a cool place. Clean up with warm soapy water or oil- based thinners. **SOAK CLOTHS IN WARM SOAPY WATER, RINSE AND HANG TO DRY AS THEY MAY SELF IGNITE IF LEFT UNATTENDED.** Keep out of reach of children. Use in a well ventilated area. If swallowed, seek medical advice.

MAINTENANCE:

A further coat should be applied every 6 - 12 months in areas of full exposure to heavy weather. For areas that are under roof, or not fully exposed, the recoat time is 12-24 months. Occasionally, as well as before re oiling your timber, a wash down is recommended to remove any sooty mould, built up dirt and dust and any other environmental pollution, which may have adhered to the timber. For heavily weathered areas, a scrub down with a solution of warm water and Organoil Wash-a-Way is recommended prior to water pressure cleaning. **If, after washing, water beads on the timber, oil is still present. Re-oiling is not yet necessary in these areas.**

CONDITIONS: OUR INFORMATION IS GIVEN IN GOOD FAITH, AND IS BASED ON RESULTS OBTAINED FROM EXPERIENCE AND TESTS. HOWEVER, AS THE ACTUAL END USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, ALL RECOMMENDATIONS AND SUGGESTIONS ARE MADE WITHOUT GUARANTEE. NO AGENT OR REPRESENTATIVE OF SALES FORCE NSW HAS THE AUTHORITY TO WAIVE OR ALTER THESE CONDITIONS.

Manufactured by SALES FORCE NSW, Sydney, Australia.