



## LIBERON FINISHING OIL

**GENERAL:** Liberon Finishing Oil is a blend of high quality oils and resins for use on all interior wood and turned woodwork. It is suitable for use on worktops, kitchen tables and bathroom furniture. It can also be applied to cork, stone and terracotta.

**PREPARATION:** Ensure the surface being treated is free of previous wax, varnish, paint or polyurethane finishes, and is clean, dry and free of dust before application of Finishing Oil.

**APPLICATION:** Shake can well before use. Apply a coat of oil using a good quality brush, or lint free cloth. Allow the oil to penetrate for up to 10 minutes. Wipe off the excess with a clean lint free cloth before the oil goes tacky. If the excess is not removed, and the surface becomes sticky, wipe with white spirit to remove the stickiness, and allow to dry before continuing.

Allow to dry for a minimum of 5 hours, then apply more coats as required following the procedure above. The more coats applied, the higher the sheen and the more durable the finish will be. A minimum of 3 coats is recommended.

For best results, gently rub the surface with ultra fine (0000) steel wool between coats.

Furniture items can be finished with Liberon Black Bison Wax for an improved lustre.

Coverage is approximately 10 square metres per litre, depending on the timber.

**IMPORTANT:** Oil finishes bring out the natural colours of the timber. An indication of the final colour will come from wetting a small area of the timber with water. We recommend always doing a test of the Finishing Oil on an inconspicuous portion of the timber, for colour, compatibility and end result.

**CLEANING AND MAINTENANCE:** Surfaces may be cleaned using a damp cloth. Spills should be wiped up immediately. For stubborn stains, a mild detergent, or plant based detergent can be used. Surfaces need to be re oiled about once a year, depending on usage.

**SAFETY:** Store Liberon Finishing Oil above 5 degrees C. Always replace lid after use, otherwise oil will deteriorate. Wash oil soaked cloths in hot soapy water, rinse and hang to dry, otherwise they may self combust. Liberon Finishing Oil is **FLAMMABLE**. Repeated exposure may cause skin dryness. Keep out of reach of children. Use in a well ventilated area. If swallowed, seek medical advice immediately, showing the container to the health professional. Contains cobalt compounds and methylethylketoxime. Liberon Finishing Oil contains max 541 g/l VOC which is within the EU limit values for finishing oils of 700 g/l.

**SIZES:** Available in 250ml, 500ml, 1 and 5 litre cans. 25 litres are available for the trade.

Liberon Products are manufactured in France, and the UK. The UK manufacturer is Liberon Ltd Mountfield Industrial Estate, New Romney, Kent.