



NATURAL HARD OIL FOR FLOORS

- DESCRIPTION:** Bio Pin Natural Hard Oil is a transparent, breathable, water resistant finish for interior timber or cork flooring. It is also designed to be used on feature timbers such as sarking, exposed beams, panelling, doors and furniture, as well as unglazed terracotta tiles. Based upon all natural ingredients, this product is safe for use on children's toys, cots, bassinets and play pens. It is food safe in accordance with European standards. (German DIN EN 71/3)
- INGREDIENTS:** Binding agent of tung oil, castor oil and modified colophony resin, orange oil, bentonite, ethanol, water and lead free drying agents. An MSDS is available upon request.
- PREPARATION:**
1. The timber must be clean, dry and free of grease and cement / gib board dust.
 2. Previous skin forming products (paint or varnish) should be completely removed by sanding prior to oiling.
 3. This product works better on smooth surfaces, rather than textured or rough sawn timbers.
 4. Sand the timber smooth with fine (180—240 grit) sandpaper. Remove any dust.
- APPLICATION:**
1. Ensure preparation has been completed first. Stir well. Follow safety instructions on the label.
 2. Using a brush or lambswool applicator, apply 1 coat evenly over the timber. After about 20 minutes, wipe any excess off with a cloth, and leave to dry for 6-8 hours, or until touch dry.
 3. Apply a second coat once the first coat is dry. Again, wipe off any excess after 20 minutes, and allow to dry.
 4. Generally, 2 coats is sufficient, but highly absorbent timbers such as pine and cedar may require an additional coat. Cork flooring may require up to 5 coats as it is so absorbent.
 5. For timber or cork flooring, follow application procedure, but after the last coat, buff the floor with a polishing machine and lambswool pad to assist drying. Walk on in 48 hours, but treat with respect, as the finish will continue to harden for about 28 days.
- COVERAGE:** Approximately 12—14 square metres per litre depending on density of timber.
- SIZES:** 750ml, 2.5 litre and 10 litre containers.
- MAINTENANCE:** Clean as required using a mild detergent, or any plant based cleaner. If the surface is worn and requires a recoat, lightly sand the timber first, clean and allow to dry before applying a thin coat of oil. Cloth in any excess and allow to dry.
- SAFETY:** Keep away from children. Store in a frost free area with the lid tightly closed. May cause an allergic reaction on skin. Use protective clothing and use in a well ventilated area. This product contains **orange oil** (CAS-Nr 8028-48-6). It is flammable and may cause lung damage if swallowed. Show can and label to the health professional, and treat symptomatically. Clean up with turpentine and hot soapy water. **CAUTION:** Wash any cloths in hot soapy water, rinse and hand to dry, as they may self ignite if left unattended.

CONDITIONS: OUR INFORMATION IS GIVEN IN GOOD FAITH, AND IS BASED ON RESULTS OBTAINED FROM EXPERIENCE AND TESTS. HOWEVER, AS THE ACTUAL END USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, ALL RECOMMENDATIONS AND SUGGESTIONS ARE MADE WITHOUT GUARANTEE. NO AGENT OR REPRESENTATIVE OF NATURAL OILS LIMITED HAS THE AUTHORITY TO WAIVE OR ALTER THESE CONDITIONS.

Manufactured in Germany by Biopin, Linumweg 1-8, Jever.

Supplied by Natural Oils Ltd, P O Box 25 352, St Heliers, Auckland.

www.naturaloils.co.nz