



HARD BURNISHING OIL

- DESCRIPTION:** A clear oil which will highlight the natural character and colour of the timber with minimal darkening or yellowing. Based on genuine, "unmodified" Tung Nut Oil formulated with other highly refined plants oils; this product provides excellent sealing and efficient curing. Specifically designed for finishing by power friction (wet-sanding/burnishing).
- USES:** For the finishing of wood turned articles such as bowls and platters etc, as well as timber floors, benchtops and tabletops.
- INGREDIENTS:** Tung nut oil, super grade gum turpentine (pine wood oil) and citrus peel extract.
- PREPARATION:**
1. Previous skin forming products (paint/varnish etc) should be completely removed by sanding prior to oiling.
 2. If accessible during the construction or installation process, it is recommended to coat the rear and/or end grain of the timber with one coat of oil.
 3. Ensure the timber is clean and free from dirt and dust
- APPLICATION:** Specific instructions are available for the finishing of benchtops etc. (using a random orbital sander), and for floor finishing (using a floor sanding machine). **Please refer to the data sheets "General Burnishing Instructions" or "Traditional Timber Floor Finishing". DO NOT attempt these applications without the correct equipment.**
- COVERAGE:** (Approximately per coat and depending on timber type)
- | | |
|----------------|---------------------------------|
| Hardwoods..... | 12 – 18 square metres per litre |
| Softwoods..... | 8 – 10 square metres per litre |
- SIZES:** 500ml and 1 litre for Woodcraft use.
4 litre and 10 litre containers for the trade.
- MAINTENANCE:** For items incurring regular and heavy use, e.g. kitchen or laundry benchtops, re-apply the Hard Burnishing Oil every 6 - 12 months. For the first year, and also for very heavily used items, maintain the article monthly, by dampening a cloth with the oil, wiping over the entire surface and then, using a dry cloth, immediately cloth off. For items which do not incur heavy use, e.g. sideboards, use the wipe on/wipe off process above only if the timber looks as if it needs rejuvenation. Typically only re-apply oil every 1-5 years – depending on the items wear and tear.
- For **repair** of heavily worn surfaces, sand the timber and re-apply the Hard Burnishing Oil using the burnishing technique. (Refer to specific application instructions).
- SAFETY:** Store with lid tightly closed in a cool place. Clean up with oil-based thinners and warm soapy water. **SOAK CLOTHS IN WARM SOAPY WATER, RINSE AND HANG TO DRY AS THEY MAY SELF IGNITE IF LEFT UNATTENDED.** Keep out of reach of children. Use in a well ventilated area. If swallowed, seek medical advice.
- FLAMMABILITY:** No flammability rating - more than 200 degrees Celsius.

CONDITIONS: OUR INFORMATION IS GIVEN IN GOOD FAITH, AND IS BASED ON RESULTS OBTAINED FROM EXPERIENCE AND TESTS. HOWEVER, AS THE ACTUAL END USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, ALL RECOMMENDATIONS AND SUGGESTIONS ARE MADE WITHOUT GUARANTEE. NO AGENT OR REPRESENTATIVE OF SALES FORCE NSW HAS THE AUTHORITY TO WAIVE OR ALTER THESE CONDITIONS.

Manufactured by SALES FORCE NSW, Sydney, Australia.