



OSMO Wood Protector

General:

A clear matt finish wood primer and preservative for interior and exterior timbers. Specifically designed for timbers which are susceptible to blue stain and mould (such as pine) which are being used in areas of damp and high humidity like bathrooms, laundries and window frames. Being biocide free, it is suitable for use on children's toys or playground equipment.

Based on natural oils and waxes, OSMO Wood Protector is extremely water repellent. It is compatible with all other OSMO wood finishes except "One Coat".

Note: Do not apply under water based stains.

Preparation:

Wood Protector is most suited for new timbers. If applying to an existing timber surface, the wood must be clean and dry with any old stains, paints and varnishes etc completely removed by sanding.

If applying another OSMO wood finish over the cured Wood Protector, it is recommended that the timber's surface be prepared in accordance with that product's data sheet, prior to application of Wood Protector.

Coverage: Approximately 8 square metres per litre—depending on the timber.

Application:

Designed to be used straight from the can. **Do not thin**, but stir well. Wood Protector can be brushed or dipped. (Dipping time approximately 2 minutes). Apply generously, and wherever possible, coat all sides, edges and end grains of the timber.

Leave to dry for approximately 24 hours, ensuring the area is well ventilated. Apply the finish coat (preferably and OSMO product) after 48 hours has elapsed.

Ingredients:

Natural vegetable oils and waxes, water repellent and anti corrosive additives, siccatives, disaromatised white spirit (benzene free). Finish is safe for man, plant and animal once cured. Ingredients meet the purity demands of the European Pharmacopoeia. Complies with German Norm DIN 53160 (fast against saliva and perspiration) and EURO Norm EN71 being suitable for children's toys. A Material Safety Data Sheet for Wood Protector is available upon request.

Cleanup, Storage and Safety:

Clean brushes with white spirit, or similar solvent. Afterwards, wash in hot soapy water and rinse well. Wash any cloths used in hot soapy water, rinse well and hang to dry, as they may self combust. Dispose of unused product in the appropriate manner.

Unopened cans can be stored up to 5 years. Once opened, use within 12 months. Frost proof.

Keep out of reach of children. Do not apply in the presence of naked flames, hot surfaces or live exposed electrical wiring. Ensure adequate ventilation during application and while the finish dries. This product contains a benzene free, low odour mineral spirit as the solvent. In case of contact with the eyes, rinse immediately with fresh cold water. Contains 2-butanonoxime, which may produce an allergic reaction. If swallowed, seek medical advice.

Flammable: Flashpoint Setaflash ASTM D 55 degrees Celsius. (German DIN 4102, class B2: normal inflammability)

Manufactured by Ostermann & Scheiwe GmbH & Co. KG, Munster, Germany